

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 December 2005 (22.12.2005)

PCT

(10) International Publication Number
WO 2005/122381 A1

(51) International Patent Classification⁷: **H02N 2/00**

(74) Agent: WATANABE, Toshihiko; 5 Mori Bldg. 8th Floor,
17-1, Toranomom 1-chome, Minato-ku, Tokyo 105-0001
(JP).

(21) International Application Number:
PCT/JP2005/010989

(22) International Filing Date: 9 June 2005 (09.06.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-171641 9 June 2004 (09.06.2004) JP

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM,
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): CANON
KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko,
Ohta-ku, Tokyo 146-8501 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): KOJIMA,
Nobuyuki [JP/JP]; Canon Kabushiki Kaisha, 3-30-2,
Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP). KITA-
JIMA, Satoru [JP/JP]; Canon Kabushiki Kaisha, 3-30-2,
Shimonaruko, Ohta-ku, Tokyo 146-8501 (JP).

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: VIBRATION WAVE DRIVEN APPARATUS AND VIBRATOR



(57) Abstract: A vibration wave driven apparatus which makes it possible to secure a required component accuracy obtained by machining and can increase a power ratio to the size of the apparatus. A plurality of contact parts are formed on one surface of an elastic vibration plate of a vibrator, and are disposed in contact with a friction member of a slider. A piezoelectric element plate is joined to the other surface of the vibration plate. Thinner parts as recessed parts are formed in the vibration plate at locations other than the contact parts, whereby the vibration plate is disposed in contact with the friction member of the slider at the contact parts.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.